

Tiandy

لیست قیمت رسمی اسفند ۱۴۰۳

تارتن دژ آریانا

نمایندگی مرکزی محصولات تیاندی

تمامی کالاها دارای 36 ماه گارانتی معتبر

۰۲۱-۸۸۵۰۰۰۲۰





تیاندی (Tiandy)

- دارنده رتبه هفتم جهان
- اولین ارائه دهنده فناوری Starlight (دید در شب رنگی)
- پیشرو در ارائه خدمات و محصولات هوشمند

Tiandy

ویژگی های برند تیاندی:

- انتقال تصویر آسان (P2P) بدون نیاز به IP استاتیک ✓
- دارای 3 سال گارانتی شرکتی پارس ارتباط ✓
- دارای خط تولید در داخل کشور ✓
- مورد تایید سازمان ها و ارگان های دولتی ✓
- بهترین کیفیت با قیمت مناسب ✓
- پشتیبانی از پروتکل ONVIF ✓
- دید در شب رنگی با حداقل لوکس نوری (0.0008) ✓



	1	2	3	4	5	6
Tiandy	TC-C32QN	TC-C32GN	TC-C32WS	TC-C32WP	TC-C32XN	TC-C32HN
	I3/E/Y/2.8mm/V5	I5/E/Y/C/2.8mm	I5/E/Y/M/4mm/V4.0	I5W/E/Y/M/2.8mm/V4.2	I3/E/Y/2.8mm/V5	I3/E/Y/C/2.8mm/V4.1

Tiandy



Price (Rials)	۲۴,۰۰۰,۰۰۰	Call	۵۰,۰۰۰,۰۰۰	۶۳,۰۰۰,۰۰۰	۲۴,۰۰۰,۰۰۰	۲۶,۴۰۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Max Resolution	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)
Sensor Size	1/2.9"	1/2.8"	1/2.8"	1/2.8"	1/2.8"	1/2.9"
Lens	2.8mm	2.8mm	4mm	2.8mm	2.8mm	2.8mm
Viewing Angle	102.8°	99.7°	85.1°	100.6°	99.7°	97.4°
Night Vision Distance	IR 30 M	IR 50 M	IR 50 M	IR 50 M/ Color	IR 30 M	IR 30 M
Dynamic Range	DWDR	DWDR	WDR 120db	WDR 120db	DWDR	DWDR
Built in Mic	Yes	Yes	Yes	Yes	Yes	Yes
SD Card Support	No	No	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	No
Reset Button	N/A	N/A	Yes	Yes	Yes	N/A
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Protection	IP67	IP67	IP67	IP67	IP67	IP66
VCA/ Feature	Tripwire, Perimeter	Tripwire, Perimeter	Tripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Parking, People Counting, Crowded, On Duty Detection, Video Abnormal, Audio Abnormal, Heatmap, Face Capture(Face Detection), Human/Vehicle Classification	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Perimeter	Tripwire, Perimeter
	TC-C32QN SPEC: I3/E/Y/2.8mm/V5	TC-C32GN SPEC: I5/E/Y/C/2.8mm	TC-C32WS SPEC: I5/E/Y/M/4mm/V4.0	TC-C32WP SPEC: I5W/E/Y/M/2.8mm/V4.2	TC-C32XN SPEC: I3/E/Y/2.8mm/V5	TC-C32HN SPEC: I3/E/Y/C/2.8mm/V4.1

	7	8	9	10	11	12
Tiandy	TC-C32XP	TC-C32XP	TC-C34UP	TC-C34WS	TC-C34HS	TC-C34HS
	W/E/Y/2.8mm/V4.1	I3W/E/Y/2.8mm/V4.2	W/E/Y/M/4mm/V4.0	I5W/E/Y/M/2.8mm/V4.2	I3/E/Y/C/2.8mm/V4.0	I3/E/Y/C/SD/2.8mm

Tiandy



Price (Rials)	۴۲,۵۰۰,۰۰۰	۴۵,۵۰۰,۰۰۰	۱۰۵,۰۰۰,۰۰۰	call	call	۶۱,۰۰۰,۰۰۰
Camera Type	Dome	Dome	Bullet	Bullet	Dome	Dome
Max Resolution	2MP(1920x1080@25fps)	2MP(1920x1080@25fps)	4MP(2560x1440@25fps)	4MP(2560x1440@25fps)	4MP(2560x1440@15fps)	4MP(2560x1440@15fps)
Sensor Size	1/2.8"	1/2.8"	1/1.8"	1/2.8"	1/2.7"	1/2.7"
Lens	2.8mm	2.8mm	4mm	2.8mm	2.8mm	2.8mm
Viewing Angle	99.7°	104.9°	92.1°	92.1°	103.4°	99.7°
Night Vision Distance	Color 15~20M	IR 30 M/ Color 15 M	Color 20~30 M	IR 50 M/ Color 15 M	IR 30 M	IR 30 M
Dynamic Range	WDR 120db	WDR 120db	WDR 120db	WDR 120db	WDR 120db	DWDR
Built in Mic	Yes	Yes	Yes	No	Yes	Yes
SD Card Support	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	No	Yes (Up to 512G)
Reset Button	Yes	Yes	Yes	Yes	N/A	N/A
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Protection	IP67	IP66	IP67	IP67	IP66	IP66
VCA/ Feature	Tripwire, Perimeter	Tripwire, Double Tripwire, Perimeter, AGC, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Perimeter	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC
Click for Details	TC-C32XP SPEC: W/E/Y/2.8mm/V4.1	TC-C32XP SPEC: I3W/E/Y/2.8mm/V4.2	TC-C34UP SPEC: W/E/Y/M/4mm/V4.0	TC-C34WS SPEC: I5W/E/Y/M/2.8mm/V4.2	TC-C34HS SPEC: I3/E/Y/C/2.8mm/V4.0	TC-C34HS SPEC: I3/E/Y/C/SD/2.8mm

	13	14	15	16	17	18
Tiandy	TC-C34XS	TC-C35WS	TC-C35US	TC-C35TS	TC-C35KS	TC-C35KS
	I3W/E/Y/2.8mm/V4.2	I5/E/Y/M/2.8mm/V4.0	I8/A/E/Y/M/C/H/2.7-13.5mm/A/E/Y/M/H/2.7-13.5mm/V4		I3/E/Y/2.8mm/V4.0	I3/E/Y/M/H/2.8mm/V4.0

Tiandy



Price (Rials)	۴۹,۵۰۰,۰۰۰	۸۴,۶۲۰,۰۰۰	۱۲۹,۵۰۰,۰۰۰	call	۷۹,۵۰۰,۰۰۰	۱۲۵,۰۰۰,۰۰۰
Camera Type	Dome	Bullet	Bullet	Bullet	Dome	Dome
Max Resolution	4MP(2592x1520@25fps)	5MP(2592x1944@20fps)	5MP(2592x1944@20fps)	5MP(2592x1944@20fps)	5MP(2592x1944@20fps)	5MP(2592x1944@20fps)
Sensor Size	1/2.8"	1/2.8"	1/2.8"	1/2.8"	1/2.8"	1/2.8"
Lens	2.8mm	2.8mm	2.7mm-13.5mm Motorized	2.7mm-13.5mm Motorized	2.8mm	2.8mm
Viewing Angle	94.7°	94.7°	96.2°~29.2°	94.2°~29.3°	94.7°	95.6°
Night Vision Distance	IR 30 M/ Color 15 M	IR 50 M	IR 80 M	Starlight/IR 80 M	Starlight/IR 30M	Starlight/IR 30M
Dynamic Range	WDR 120db	WDR 120db	WDR 120db	WDR 120db	WDR 120db	WDR 120db
Built in Mic	Yes	Yes	Yes	Yes	Yes	Yes
SD Card Support	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)
Reset Button	Yes	Yes	Yes	Yes	Yes	Yes
Video Compression	S+265/H.265/H.265	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Protection	IP67	IP67	IP67	IP67	IP67,IK10	IP67,IK10
VCA/ Feature	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, BLC, 3D DNR, HLC, Corridor Format	Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Parking, Crowded, People Counting, Crowded, On Duty Detection, Video Abnormal, Audio Abnormal, Heatmap, Face Capture(Face Detection), Safety Helmet Detection, Human/Vehicle Classification
Click for Details	TC-C34XS SPEC: I3W/E/Y/2.8mm/V4.2	TC-C35WS SPEC: I5/E/Y/M/2.8mm/V4.0	TC-C35US SPEC: I8/A/E/Y/M/C/H/2.7-13.5	TC-C35TS SPEC: I8/A/E/Y/M/H/2.7-13.5/V4.1	TC-C35KS SPEC: I3/E/Y/2.8mm/V4.0	TC-C35KS SPEC: I3/E/Y/M/H/2.8mm/V4

	19	20	21	22	23	24
Tiandy	TC-C35MS I3/A/E/Y/M/C/H/2.7-13.5mm/ V4.0	TC-C38WS I5/E/Y/M//2.8mm/V4.0	TC-C38WS I5/E/Y/M//4mm/V4.0	TC-C38XS I3/E/Y/M/2.8mm/V4.0	TC-C38KS I3/E/Y/2.8mm/V4.0	TC-C38MS I5/A/E/Y/M/H/2.7-13.5/V4.0

Tiandy



Price (Rials)	۱۲۸,۵۰۰,۰۰۰	۱۲۳,۶۰۰,۰۰۰	۱۲۳,۶۰۰,۰۰۰	۹۸,۰۰۰,۰۰۰	۱۱۹,۸۶۰,۰۰۰	۲۳۰,۰۰۰,۰۰۰
Camera Type	Dome	Bullet	Bullet	Dome	Dome	Dome
Max Resolution	5MP(2592x1944@20fps)	8MP(3840x2160@20fps)	8MP(3840x2160@20fps)	8MP(3840x2160@20fps)	8MP(3840x2160@20fps)	8MP(3840x2160@25fps)
Sensor Size	1/2.8"	1/2.8"	1/2.8"	1/2.8"	1/2.8"	1/2.8"
Lens	2.7-13.5mm Motorized	2.8mm	4mm	2.8mm	2.8mm	2.7-13.5mm Motorized
Viewing Angle	96.2°~29.2°	100°	86.6°	100.1°	101.3°	102.7°~29°
Night Vision Distance	IR 30M	IR 50 M	IR 50 M	IR 30 M	IR 30 M	Starlight/IR 50 M
Dynamic Range	WDR 120db	WDR 120db	WDR 120db	WDR 120db	WDR 120db	WDR 120db
Built in Mic	Yes	Yes	Yes	Yes	Yes	Yes
SD Card Support	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 128G)	Yes (Up to 512G)
Reset Button	Yes	Yes	Yes	Yes	Yes	Yes
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Protection	IP66,IK10	IP67	IP67	IP67	IP67,IK10	IP67,IK10
VCA/ Feature	Tripwire, Perimeter, BLC, 3D DNR, HLC	Tripwire, Perimeter	Tripwire, Perimeter	Tripwire, Perimeter, BLC, 3D DNR, HLC, Corridor Format	Tripwire, Perimeter	Tripwire, Perimeter, BLC, 3D DNR, HLC, Corridor Format
Click for Details	TC-C35MS SPEC: I3/A/E/Y/M/C/H/2.7-13.5/V4	TC-C38WS SPEC: I5/E/Y/M//2.8mm/V4.0	TC-C38WS SPEC: I5/E/Y/M//4mm/V4	TC-C38XS SPEC: I3/E/Y/M/2.8mm/V4.0	TC-C38KS SPEC: I3/E/Y/2.8mm/V4.0	TC-C38MS SPEC: I5/A/E/Y/M/H/2.7-13.5/V4

	25	26	27	28	29
Tiandy	TC-H324S	TC-H326S	TC-H356S	TC-C32WN	TC-C32KN
	Spec:25X/I/E	Spec:33X/I/E+/A/V3.0	Spec:30X/I/E++/A/V3.0	I5/Y/WIFI/4mm/V4.0	I3/Y/WIFI/2.8mm

Tiandy



Price (Rials)	۳۹۰,۰۰۰,۰۰۰	۶۳۰,۰۰۰,۰۰۰	۸۵۰,۰۰۰,۰۰۰	۴۳,۵۰۰,۰۰۰	۴۲,۵۰۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	Bullet	Dome
Max Resolution	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)	5MP(2880×1620@25fps)	2MP(1920×1080@25fps)	2MP(1920×1080@25fps)
Sensor Size	1/2.8"	1/2.8"	1/2.7"	1/2.8"	1/2.8"
Lens	4.8~120mm Varifocal	4.6~152mm Varifocal	4.7~141mm Varifocal	4mm	2.8mm
Viewing Angle	58.5°~2.8°	60.5°~2.3°	61.9°~2.5°	83.3°	98.5°
Night Vision Distance	IR 150 M	IR 150 M	IR 150 M	IR 50 M	IR 50 M
Dynamic Range	WDR 140db	WDR 140db	WDR 120db	DWDR	DWDR
Built in Mic	No	No	No	Yes	Yes
SD Card Support	Yes (Up to 512G)	Yes (Up to 128G)	Yes (Up to 512G)	Yes (Up to 512G)	Yes (Up to 512G)
Reset Button	Yes	Yes	Yes	Yes	Yes
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Protection	IP66	IP66	IP66	IP67	IP67, IK10
VCA/ Feature	Tripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Video Abnormal, On-duty detection, Face Detection, Face Capture	Tripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Parking, Video Abnormal, Audio Abnormal, Heatmap	Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Lost; Heatmap; Loitering; Running; Parking; People Counting; Crowded; Safety Helmet Detection;	BLC/3D DNR/HLC	BLC/3D DNR/HLC
Click for Details	TC-H324S SPEC:25X/I/E	TC-H326S SPEC:33X/I/E+/A/V3.0	TC-H356S SPEC:30X/I/E++/A/V3.0	TC-C32WN SPEC:I5/Y/WIFI/4mm/V4.0	TC-C32KN SPEC:I3/Y/WIFI/2.8mm

	30	31	32	33	34	35
Tiandy	TC-R3105	TC-R3105	TC-R3105	TC-R3108	TC-R3110	TC-R3110
	Spec:I/B/P/L	Spec:I/B/L/EU	Spec:I/B/P/L/S	Spec:I/B/V2.0	Spec:I/B/V3.0	Spec : I/B/P8/L/S

Tiandy



Price (Rials)	۴۷,۰۰۰,۰۰۰	۳۹,۰۰۰,۰۰۰	۴۴,۵۰۰,۰۰۰	۴۳,۰۰۰,۰۰۰	۶۹,۰۰۰,۰۰۰	۵,۷۰۰,۰۰۰
Video Input	5-ch	5-ch	5-ch	8-ch	10-ch	10-ch
Recording Resolution	6MP/5MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	6MP/5MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	6MP/5MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	6MP/5MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	5MP/4MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	6MP/5MP/3MP/1080P/UXGA /720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
PoE port	4-port	-	4-port	-	-	8-port
HDD	1 up to 10TB	1 up to 10TB	1 up to 10TB	1 up to 10TB	1 up to 10TB	1 up to 10TB
Input Bandwidth	60Mbps	50Mbps	60Mbps	60Mbps	40Mbps	50Mbps
Output Bandwidth	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M
Video Output	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Click for Details	TC-R3105 SPEC: I/B/P/L	TC-R3105 SPEC:I/B/L/EU	TC-R3105 SPEC: I/B/P/L/S	TC-R3108 SPEC:I/B/V2.0	TC-R3110 Spec:I/B/V3.0	TC-R3110 SPEC : I/B/P8/L/S

	36	37	38	39	40	41
Tiandy	TC-R3220	TC-R3220	TC-R3432	TC-R3440	TC-R3440	TC-R3840
	Spec:I/B/K/V3.0	Spec:I/B/P16/K/V3.0	Spec:I/B/K/V3.1	Spec:I/B/N	Spec:I/B/N/H/C	Spec:I/B/N

Tiandy



Price (Rials)	۲۰۵,۰۰۰,۰۰۰	۲۱۸,۰۰۰,۰۰۰	۲۸۷,۰۰۰,۰۰۰	۴۹۸,۰۰۰,۰۰۰	call	۶۵۰,۰۰۰,۰۰۰
Video Input	20-ch	20-ch/16P	32-ch	40-ch	40-ch	40-ch
Recording Resolution	8MP/6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	8MP/6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
PoE port	-	16-port	-	-	-	-
HDD	2 up to 10TB	2 up to 10TB	4 up to 10TB	4 up to 10TB	4 up to 10TB	8 up to 10TB
Input Bandwidth	120Mbps	120Mbps	160Mbps	400Mbps	400Mbps	400Mbps
Output Bandwidth	100Mbps	100Mbps	48Mbps	400Mbps	400Mbps	200Mbps
Network Interface	1 RJ45 100M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Video Output	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 4K 1 Port VGA	2 Port HDMI : 4K 2 Port VGA
Video Compression	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264	S+265/H.265/H.264
Click for Details	TC-R3220 SPEC:I/B/K/V3.0	TC-R3220 SPEC:I/B/P16/K/V3.0	TC-R3432 SPEC:I/B/K/V3.1	TC-R3440 SPEC: I/B/N	TC-R3440 SPEC:I/B/N/H/C	TC-R3840 SPEC:I/B/N/V4.0

42

Tiandy

TC-R3880

Spec:I/B/N/V4.0

Tiandy



tiandy-cctv.com

Price (Rials)	^+++,,,+++
Video Input	80-ch
Recording Resolution	12MP/8MP/6MP/5MP/4MP/ 3MP/1080P/UXGA/720P/VGA /4CIF/DCIF/2CIF/CIF/QCIF
Playback Capability	-
HDD	8 up to 24TB
Input Bandwidth	640Mbps
Output Bandwidth	320Mbps
Network Interface	2 RJ45 1000M
Video Output	2 Port HDMI : 4K 2 Port VGA
Video Compression	S+265/H.265/H.264
Click for Details	TC-R3880 SPEC:I/B/N/V4.0

tiandy-cctv.com