



## TC-C35US Spec:LK/I5W/E/Y/M/S/2.8mm/V5.0

5MP Fixed Color Maker Bullet Camera

Lite Series



### KEY FEATURES

- Metal housing
- Up to 5MP, 2880 × 1620 @ 30fps
- S+265/H.265/H.264B/H.264M/H.264H
- Color: 0.002Lux@ (F1.6, AGC ON), B/W: 0Lux with IR
- IR range up to 50m
- Built-in Mic
- Support microSD/microSDHC/microSDXC card, up to 512GB
- Support human/vehicle classification
- Operating conditions -40°C ~ 65°C (-40°F ~ 149°F), ≤95%RH
- DC12V ± 25%, Max. 8W, PoE: IEEE 802.3af, Max. 9W
- IP67



Tiandy Technologies Co., Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

**Tiandy Technologies Co., Ltd.**

Email: [sales@tiandy.com](mailto:sales@tiandy.com)

Tel: +86-22-58596065

Website: [en.tiandy.com](http://en.tiandy.com)


Fax: +86-22-58596048

SPECIFICATIONS

| Camera               |                                                                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor         | 1/2.7"CMOS                                                                                                                                                |
| Min. Illumination    | Color:0.002Lux@(F1.6,AGC ON),B/W:0Lux with IR                                                                                                             |
| Shutter Time         | 1s~1/100000s                                                                                                                                              |
| Day&Night            | IR-cut filter with auto switch (ICR)                                                                                                                      |
| Smart IR             | Yes                                                                                                                                                       |
| WDR                  | 120dB                                                                                                                                                     |
| S/N                  | >39dB                                                                                                                                                     |
| Angle Adjustment     | 0~360°(P); 0~90°(T); 0~360°(R)                                                                                                                            |
| Lens                 |                                                                                                                                                           |
| Lens Type            | Fixed focal lens                                                                                                                                          |
| Focal Length         | 2.8mm                                                                                                                                                     |
| Lens Mount           | M12                                                                                                                                                       |
| Aperture Range       | F1.6                                                                                                                                                      |
| Aperture Type        | Fixed                                                                                                                                                     |
| Field of View        | 109°(H); 59°(V); 125.4°(D)                                                                                                                                |
| DORI Distance        | Detect:56m<br>Observe:22m<br>Recognize:11m<br>Identify:5.6m                                                                                               |
| Illuminator          |                                                                                                                                                           |
| IR LEDs              | 4                                                                                                                                                         |
| IR Distance          | Up to 50m                                                                                                                                                 |
| Wavelength           | 850nm                                                                                                                                                     |
| White LEDs           | 4                                                                                                                                                         |
| Whitelight Distance  | 15m                                                                                                                                                       |
| Compression Standard |                                                                                                                                                           |
| Video Compression    | S+265/H.265/H.264B/H.264M/H.264H                                                                                                                          |
| Video Bit Rate       | 32k~6Mbps                                                                                                                                                 |
| Audio Compression    | G.711A/G.711U/ADPCM_D                                                                                                                                     |
| Audio Sampling Rate  | 8kHz/32kHz/48kHz                                                                                                                                          |
| Image                |                                                                                                                                                           |
| Max. Resolution      | 5MP,2880×1620@30fps                                                                                                                                       |
| Main Stream          | PAL:25fps(2880×1620, 2688×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720)<br>NTSC:30fps(2880×1620, 2688×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720) |
| Sub Stream           | PAL:25fps( 704×576, 704×288, 352×288)<br>NTSC:30fps(1704×480, 704×240, 352×240)                                                                           |
| BLC                  | Yes                                                                                                                                                       |
| HLC                  | Yes                                                                                                                                                       |
| AGC                  | Yes                                                                                                                                                       |
| 3D DNR               | Yes                                                                                                                                                       |

|                                      |                                                                                                                                                                           |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| White Balance                        | Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance                                                                 |
| ROI                                  | 8 rectangular static areas                                                                                                                                                |
| OSD                                  | Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48/64*64                       |
| Privacy Mask                         | 4 black static areas                                                                                                                                                      |
| Defog                                | Yes                                                                                                                                                                       |
| <b>Feature</b>                       |                                                                                                                                                                           |
| General Alarm                        | Motion Detection; Mask Alarm                                                                                                                                              |
| Exceptions Alarm                     | Disk Full; Disk R/W Error; IP Address Conflict                                                                                                                            |
| Linkage Method                       | Trigger Warmlight; Trigger Recording; Trigger Capture; Notify Surveillance Center                                                                                         |
| Video Analytics                      | Human/Vehicle Classification; Tripwire; Perimeter                                                                                                                         |
| Rules of Behavior Analyse In 1 Scene | 2                                                                                                                                                                         |
| <b>Network</b>                       |                                                                                                                                                                           |
| ANR                                  | Yes                                                                                                                                                                       |
| Protocols                            | HTTP; HTTPS; TCP/IP; UDP; UPnP; ICMP; DHCP; DNS; DDNS; Easy DDNS; NTP; TLS v1.2; SSL; QoS; IPv4; SSH; Unicast; ARP; FTP                                                   |
| System Compatibility                 | P2P(Mutually exclusive with Profile G); ONVIF(Profile S/T/G) ; SDK; CGI; Milestone; RTSP                                                                                  |
| Remote Connection                    | ≤2                                                                                                                                                                        |
| Client                               | Easy7 VMS                                                                                                                                                                 |
| Moblie Client                        | EasyLive Plus                                                                                                                                                             |
| Web                                  | IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+                                                                                                                          |
| <b>Interface</b>                     |                                                                                                                                                                           |
| Communication Interface              | 1*RJ-45 (10/100 Base-T)                                                                                                                                                   |
| Built-in Mic                         | Yes                                                                                                                                                                       |
| Reset Button                         | Yes                                                                                                                                                                       |
| On-board Storage                     | Support microSD/microSDHC/microSDXC card,up to 512GB                                                                                                                      |
| RTC                                  | Yes                                                                                                                                                                       |
| <b>General</b>                       |                                                                                                                                                                           |
| Web Client Language                  | 18 languages<br>Traditional Chinese/English/Spanish/Korean/Italian/Turkish/Russian/Thai/French/Polish/Dutch/Hebrew/Arabic/Vietnamese/German/Ukrainian/Portuguese/Albanian |
| Operating Temperature                | -40°C~65°C(-40°F~149°F)                                                                                                                                                   |
| Operating Humidity                   | ≤95%RH                                                                                                                                                                    |
| Storage Temperature                  | -40°C~65°C(-40°F~149°F)                                                                                                                                                   |
| Storage Humidity                     | 10%~95%RH(non-condensing)                                                                                                                                                 |
| Power Supply                         | DC12V±25%,Max. 8W; PoE:IEEE 802.3af,Max. 9W                                                                                                                               |
| Protection                           | Surge4000V; ESD6000V; IP67                                                                                                                                                |
| Boundary Dimensions                  | 239(L)90(W)90(H)mm                                                                                                                                                        |
| Package Dimensions                   | 280(L)125(W)140(H)mm                                                                                                                                                      |
| GrossWeight                          | 1.28kg                                                                                                                                                                    |

DIMENSIONS (Unit: mm)



Assembly diagram of Junction Box



TC-P54BM Spec:V5

A36