

AK SERIES				
۱	TC-C320N Spec:I3/E/Y/C/2.8MM/V2.0		Metal+Plastic Housing-Up to 1920x1080@30fps -S+265/H.265/H.264-Min. illumination Color: 0.04Lux@F2.2 -Smart IR, IR Range: 30m -Built-in Mic -Operating Conditions -30°~60°, 0~95% RH-POE -Support motion detection	۲۲,۰۰۰,۰۰۰
۲	TC-C321N Spec:I3/E/Y/C/2.8MM/V2.0		Plastic Housing-Up to 1920x1080@30fps -S+265/H.265/H.264-Min. illumination Color: 0.04Lux@F2.2 -Smart IR, IR Range: 30m -Built-in Mic -Operating Conditions -30°~60°, 0~95% RH -POE, IP67 -Support motion detection	۲۲,۰۰۰,۰۰۰
Spark-Series				
۳	TC-C32XN Spec:I3W/E/Y/ 2.8mm/V4.2		Metal+plastic housing Up to 2MP,1920x1080@30fps S+265/H.265/H.264B/H.264M/H.264H Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR. IR range up to 30m 1xBuilt-in Mic Operating conditions -30C~60C*(-22F~140F), ≤95%RH DC12V±25%,Max. 6.5W, PoE:IEEE 802.3af,Max. 7W	۴۵,۰۰۰,۰۰۰
۴	TC-C34QN Spec:I3/E/Y/ 2.8MM/4mm/V5.0		-Metal+Plastic Housing-Up to 2560x1440@20fps -S+265/H.265/H.264-Min. illumination Color: 0.02Lux@F1.6 -Smart IR, IR Range: 30m-Built-in Mic -Operating Conditions -30°~60°, 0~95% RH -POE, IP67	۵۱,۰۰۰,۰۰۰
۵	TC-C34QN Spec:I5W/E/Y/2.8MM/V4.2		4MP Fixed Starlight IR Bullet Camera, -Metal+Plastic Housing -Up to 2688X1520@25fps-S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F1.6 -2 Warm lights, 15m -Smart IR, IR Range: 50m -Built-in Mic -Operating Conditions -30°~60°, 0~95% RH -POE, IP67	۵۹,۲۰۰,۰۰۰
۶	TC-C34XN Spec:I3W/E/Y/2.8MM/V4.2		4MP Fixed Starlight IR Turret Camera -Metal+Plastic Housing-Up to 2688X1520@25fps -S+265/H.265/H.264-Min. illumination Color: 0.02Lux@F1.6 -2 Warm lights, 15m, -Smart IR, IR Range: 30m-Built-in Mic -Operating Conditions -30°~60°, 0~95% RH -Support tripwire and perimeter -DC12V,POE	۵۶,۰۰۰,۰۰۰
۷	TC-C34XN Spec:I3/E/Y/2.8MM/V5.0		4MP Fixed Turret Camera, -Metal+Plastic Housing-Up to 2688X1520@25fps -S+265/H.265/H.264-Min. illumination Color: 0.02Lux@F1.6 -2 Warm lights, 15m, -Smart IR, IR Range: 30m-Built-in Mic -Operating Conditions -30°~60°, 0~95% RH -Support tripwire and perimeter -DC12V,POE	۵۰,۰۰۰,۰۰۰
۸	TC-R3104 SPEC: I/B/P4/L/S		Up to 4-ch IP camera accesses Incoming/Outgoing bandwidth: 60Mbps/40Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 5MP(30fps)×1 or 1080P(30fps)×2 4-ch synchronous playback Up to 6 TB capacity for each HDD 1×HDMI output HDMI output at up to 1080P resolution 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port PoE interface, 4×RJ45, 10/100 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade	۵۳,۵۰۰,۰۰۰
۹	TC-R3108 SPEC: I/B/P8/C/Eu/L/S		 Up to 8-ch IP camera accesses Incoming/Outgoing bandwidth: 60Mbps/40Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4 4-ch synchronous playback Up to 6 TB capacity for each HDD 1×HDMI output HDMI output at up to 4K resolution 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port PoE interface, 8×RJ45, 10/100 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade	۶۸,۰۰۰,۰۰۰
W ifi-S e r i e s				
۱۰	TC-C32WN spec: I5/Y/WIFI/4MM/V4.0		2MP Fixed IR Wi-Fi Bullet Camera - Metal+Plastic Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 50m -Operating Conditions -35°C~65°C, 0~95% RH -Built-in Mic, SD Card Slot, Reset Button -Support Wi-Fi -IP67	۵۵,۰۰۰,۰۰۰
۱۱	TC-C32KN spec:I3/Y/WIFI/2.8MM		2MP Fixed IR Wi-Fi Dome Camera - Metal+Plastic Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.02Lux@F2.0 -Smart IR, IR Range: 30m -Operating Conditions -35°C~65°C, 0~95% RH -Built-in Mic, SD Card Slot, Reset Button -Support Wi-Fi -IP67, IK10	۵۰,۰۰۰,۰۰۰

Omni Camera				
۱۲	TC-C32RN Spec: I5/E/Y/QX/ 2.8mm/V4.2		Plastic housing Up to 2MP, 1920x1080@30fps S+265/H.265/H.264B/H.264M/H.264H Color: 0.02Lux@F1.6, AGC ON, B/W: 0Lux with IR IR range up to 50m 1x Built-in Mic Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH DC12V±25%, Max. 7.5W, PoE: IEEE 802.3af, Max. 8.5W IP67	۸۴,۵۰۰,۰۰۰
Super lite, Lite & Eco Series				
۱۳	TC-C32GS spec: I5/E/Y/C/SD/ 2.8MM/V4.2		2MP Fixed Starlight IR Bullet Camera, -Metal+Plastic Housing -Up to 1920x1080@30fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6, -Smart IR, IR Range: 50m -Built-In Mic -Support tripwire and perimeter -Operating Conditions -30°C~60°C, 0~95% RH -POE, IP67	۵۷,۰۰۰,۰۰۰
۱۴	TC-C32HS I3/E/Y/C/SD/2.8MM/ V4.2		2MP Fixed Starlight IR Turret Camera, -Metal+Plastic Housing -Up to 1920x1080@30fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6, -Smart IR, IR Range: 30m -Built-In Mic -Support tripwire and perimeter -Operating Conditions -30°C~60°C, 0~95% RH -POE, IP66	۵۷,۰۰۰,۰۰۰
۱۵	TC-C34GS I5/E/Y/C/SD/2.8MM/ V4.2		4MP Fixed Starlight IR Bullet Camera, -Metal+Plastic Housing -Up to 2560x1440@25fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6, -Smart IR, IR Range: 50m -Built-In Mic -Support tripwire and perimeter -Operating Conditions -30°C~60°C, 0~95% RH -POE, IP67	۶۲,۶۰۰,۰۰۰
۱۶	TC-C35WS Spec: I5/E/Y/M/2.8mm/V4.0		5MP Fixed Starlight IR Bullet Camera - Full Metal Housing -Up to 2592x1944@20fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -120dB WDR -Smart IR, IR Range: 50m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C~60°C, 0~95% RH -POE, IP67	۸۸,۰۰۰,۰۰۰
۱۷	TC-C35XS Spec: I3/E/Y/C/H/2.8MM		5MP Starlight Mini IP Turret -Up to 2592x1944@20fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 Plastic-120dB WDR -Smart IR, IR Range: 30m. IP66. Built-in Micro SD card slot, up to 512GB -Operating Conditions -40°C~60°C, 0~95% RH -POE	۸۸,۰۰۰,۰۰۰
۱۸	TC-C35KS Spec: I3/E/Y/C/H/ 2.8mm/V4.0		Metal+plastic housing Up to 5MP, 2592x1944@20fps S+265/H.265/H.264B/H.264M/H.264H Color: 0.002Lux@F1.6, AGC ON, B/W: 0Lux with IR IR range up to 30m Built-in Mic Support microSD/ microSDHC/microSDXC card, up to 512GB Operating conditions -40°C~65°C (-40°F~149°F), ≤95%RH DC12V±25%, Max. 6W, PoE: IEEE 802.3af, Max. 7W IP66, IK10	۸۲,۰۰۰,۰۰۰
۱۹	TC-C38WS Spec: I5/E/Y/M/2.8mm(4mm)/V4.0		-Full Metal Housin, -Up to 3840x2160@20fps 8MP Fixed Starlight IR Bullet Camera S+265/H.265/H.264, -Min. illumination Color: 0.003Lux@F1.6, -120dB WDR -Smart IR, IR Range: 50m, -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40	۱۳۴,۹۰۰,۰۰۰
۲۰	TC-C38KS SPEC: I3/E/Y/2.8mm/ V4.0		8MP Fixed Starlight IR Dome Camera -Metal+Plastic Housing -Up to 3840x2160@20fps S+265/H.265/H.264 -Min. illumination Color: 0.003Lux@F1.6 -120dB WDR -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -35~65°, 0~95% RH -POE, IP67, IK10	۱۱۸,۰۰۰,۰۰۰
Color Maker Series				
۲۱	TC-C32XP Spec: I3W/E/Y/2.8mm/V4.2		2MP Fixed Color Maker Turret Camera - Metal+Plastic Housing -Up to 1920x1080@30fps S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -Smart IR, IR Range: 30m -2 Warm lights, 30m -Support tripwire and perimeter -Built-in Mic, support max 512G Micro SD Card -Operating -40°C~65°C, 0~95% RH -POE, DC12V -IP66 Conditions	۴۸,۰۰۰,۰۰۰

۰۲۱۵۲۶۰۵

۲۲	TC-C35US L/K/I5W/E/Y/M/S/ 2.8MM/V5.0		Metal housing Up to 5MP,2880x1620@30fps S+265/H.265/H.264B/H.264M/H.264H Color:0.002Lux@F1.6,AGC ON),B/W:0Lux with IR range up to 50m Built-in Mic Support microSD/ microSDHC/microSDXC card,up to 512GB Support human/vehicle classification Operating conditions -40C°~65C°(-40F°~149F°), ≤95%RH DC12V±25%,Max. 8W, PoE:IEEE 802.3af,Max. 9W IP67	۱۸۲,۰۰۰,۰۰۰
۲۳	TC-C35UV Spec:W/E/Y/M/S/4MM		•Metal housing • Up to 5MP,3072x1728@30fps • S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG • Color:0.0001Lux@F1.0,AGC ON),B/W:0Lux with IR • Built-in Mic • IP67 • Support microSD/ microSDHC/ microSDXC card,up to 512GB • Support smart surveillance • Support human/vehicle classification • Operating conditions -40C°~65C°(-40F°~149F°), ≤95%RH • DC12V±25%,Max. 8W, PoE:IEEE 802.3af,Max. 9W	۱۹۹,۰۰۰,۰۰۰
Motorized Series				
۲۴	TC-C35US Spec:I8/A/E/Y/M/C/H/2.7- 13.5MM		5MP Motorized Starlight IR Bullet Camera - Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -Smart IR, IR Range: 80m -Support tripwire and perimeter -Built-in Mic, support max 512G Micro SD Card -Audio I/O 1/1, Alarm I/O 1/1 -Operating Conditions -35C°~65C°, 0~95% RH -DC12V,POE -IP67,IK10	۱۳۵,۰۰۰,۰۰۰
۲۵	TC-C35MS Spec:I3/A/E/Y/M/C/H/2.7- 13.5MM/V4.0		5MP Motorized Starlight IR Dome Camera - Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@20fps -S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6 -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Audio I/O 1/1, Alarm I/O 1/1 -Operating Conditions -35C°~60C°, 0~95% RH -POE, IP66, IK10	۱۲۹,۵۰۰,۰۰۰
۲۶	TC-C35TS Spec:I8/A/E/Y/M//H/2.7- 13.5/V4.1		Metal housing Up to 5MP,2880x1620@30fps S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG Color:0.002Lux@F1.6,AGC ON),B/W:0Lux with IR range up to 80m 1xBuilt-in Mic • Support microSD/microSDHC/microSDXC card,up to 512GB Support smart surveillance, face capture Support human/vehicle classification Operating conditions -40C°~65C°(-40F°~149F°), ≤95%RH DC12V±25%,Max. 9.5W, PoE:IEEE 802.3af,Max. 10.5W IP67	۲۲۵,۰۰۰,۰۰۰
۲۷	TC-C38TS Spec:I8/A/E/Y/M//H/2.7- 13.5/V4.0		Metal housing Up to 8MP,3840x2160@30fps S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG Color:0.002Lux@F1.6,AGC ON),B/W:0Lux with IR range up to 80m 1xBuilt-in Mic Support microSD/microSDHC/microSDXC card,up to 512GB Support smart surveillance Support human/ vehicle classification Operating conditions -40C°~65C°(-40F°~149F°), ≤95%RH DC12V±25%,Max. 9.5W, PoE:IEEE 802.3af,Max. 10.5W IP67	۲۵۵,۰۰۰,۰۰۰
۲۸	TC-C38MS Spec:I5/A/E/Y/M/H/2.7- 13.5/V4.0		•Full Metal Housing-Motorized Lens 2.7-13.5mm -Up to 3840x2160@30fps -S+265/H.265/H.264/M-JPEG-Min. illumination Color: 0.003Lux@F1.6-Smart IR, IR Range: 50m -Support Video AnalyticsSupport Human/Vehicle Classification -Built-in Mic, audio I/O 1/1, alarm I/O 2/1-Plugin Free -Operating Conditions -35C°~65C°, 0~95% RH -POE, IP67, IK10	۲۴۰,۰۰۰,۰۰۰
Panoramic				
۲۹	TC-C382V Spec:W/E/Y/S/H/2.8mm		Metal+plastic housing Up to Max. Resolution S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG Color :0.0001Lux@F1.0,AGC ON),B/W:0Lux with IR Built-in Mic, Built-in Speaker Support microSD/microSDHC/ microSDXC card, up to 512 GB Support Smart surveillance Support Human/Vehicle Classification Operating , Humidity 95% or less (no condensation) DC12V±25%,MAX 11.0W, POE 802.3at,MAX 12W IP67	۲۵۳,۰۰۰,۰۰۰
Speed Dome Series				
۳۰	TC-H324S Spec:23X/I/E/C/V3.0		•Up to 1920X1080@30fps -Min. illumination Color: 0.001Lux@F1.5 -Optical zoom: 23x, digital zoom 16x -Support Human/Vehicle Classification -Smart IR, IR Range: 150m -S+265/H.265/H.264/M-JPEG -Plugin Free -IP66	۳۵۸,۰۰۰,۰۰۰
۳۱	TC-H366V Spec:4MP/25X/IW/E/A/ 2.8mm		Up to Panorama:3840x1568@25fps Detail: 2560x1440@25fps Panorama:0.0001lux Detail:0.001Lux Panorama:S+265/H.265/H.264/M-JPEG Detail:S+265/H.265/H.264/M-JPEG Built-in Micro SD card slot, up to 512 GB Support Panorama:Smart surveillance Detail:Smart surveillance Support Panorama:Human/Vehicle Classification Detail:Human/Vehicle Classification Operating Conditions -30C°~65C°(IR OFF) -30C°~ 40C°(IR ON), 0-95% AC24V±25%/DC24V±10%, POE IEEE802.3BT IP66	۷۴۰,۰۰۰,۰۰۰
۳۲	TC-H324S Spec:25X/I/E/V3.0		2MP 25x Starlight IR PTZ Camera - Up to 1920X1080@30fps -Min. illumination Color: 0.001Lux@F1.5 -Optical zoom: 25x, digital zoom 16x -Support Human/Vehicle Classification -Smart IR, IR Range: 150m -S+265/H.265/H.264/M-JPEG -Plugin Free -IP66	۴۵۰,۰۰۰,۰۰۰

۰۲۱۵۲۶۰۵

۳۳	TC-H326S Spec:33X/I/E+/A/V3.0		2MP 33x Starlight IR POE AI PTZ Camera- Up to 1920X1080@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 33x, digital zoom 16x ·Smart IR, IR Range: 200m ·S+265/H.265/H.264/M-JPEG ·Intelligent monitoring/ Face Capture mode ·Support Human/Vehicle Classification ·Support Auto-tracking ·Plugin Free ·IP66	۶۵۰,۰۰۰,۰۰۰
۳۴	TC-H356S Spec:30X/I/E+/A/V3.0		5MP 30x Starlight IR POE AI PTZ Camera ·Support Auto-tracking ·Up to 2880x1620@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 30x, digital zoom 16x ·Smart IR, IR Range: 200m ·S+265/H.265/H.264/M-JPEG ·Intelligent monitoring/ Face Capture mode ·Support Human/Vehicle Classification ·Plugin Free ·IP66	۸۸۰,۰۰۰,۰۰۰
N V R S e r i e s				
۳۵	TC-R3105 SPEC:I/B/P/L		1 HDD 5ch PSE NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K resolution HD Storage ·1 SATA interface, up to 8TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface ·PoE Port: 4xRJ45 self-adaptive 10/100 Mbps network interfaces	۵۶,۰۰۰,۰۰۰
۳۶	TC-R3108 Spec:I/B/V2.0		1 HDD 8ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K resolution HD Storage ·1 SATA interface, up to 8TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	۴۹,۰۰۰,۰۰۰
۳۷	TC-R3110 SPEC : I/B/L/V1.1		·Up to 10-ch IP camera accesses ·Incoming/Outgoing bandwidth: 60Mbps/40Mbps ·S+265, H.265, S+264, H.264 video formats ·Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4 ·4-ch synchronous playback ·1HDD. Up to 8 TB capacity for each HDD ·Simultaneous HDMI and VGA outputs ·HDMI output at up to 4K resolution ·1xRJ-45, 10/100 Mbps self-adaptive Ethernet port ·S+ 265 compression effectively reduces the storage space by up to 75% ·Support cloud upgrade	۵۹,۸۰۰,۰۰۰
۳۸	TC-R3120 Spec:I/B/V3.0		Up to 20-ch IP camera accesses Incoming/Outgoing bandwidth: 80Mbps/80Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 8MP(30fps)×1 or 1080P(30fps)×4 Up to 16 channels-ch synchronous playback ·1 HDD. Up to 10 TB capacity for each HDD ·Simultaneous HDMI and VGA outputs HDMI output at up to 4K resolution 1xRJ-45, 10/100 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade	۱۲۵,۰۰۰,۰۰۰
۳۹	TC-R3220 Spec:I/B/K/V3.1		2HDD 20ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 20-channel input ·Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output ·HDMI and VGA simultaneous output ·HDMI Video output at up to 4K (3840×2160) resolution HD Storage ·2 SATA interfaces, up to 10TB for each HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	۲۲۰,۰۰۰,۰۰۰
۴۰	TC-R3220 Spec:I/B/P16/K/V3.0		2HDD 20ch PSE NVR ·HD Input ·Plug and play ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 20-channel input ·16 PoE ports ·Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K (3840 × 2160) resolution HD Storage ·2 SATA interfaces, up to 10TB for each HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100/1000 Mbps network interface ·PoE Port: 16xRJ45 self-adaptive 10/100 Mbps network interfaces	۲۴۳,۰۰۰,۰۰۰
۴۱	TC-R3240 Spec:I/B/N/H/V4.0		Up to 40-ch IP camera accesses Incoming/Outgoing bandwidth: 400Mbps/400Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×16 Up to 16 channels-ch synchronous playback ·2 HDD. Up to 10 TB capacity for each HDD ·Independent HDMI and VGA outputs HDMI output at up to 4K resolution 2xRJ-45, 10/100/1000 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade	۳۹۹,۰۰۰,۰۰۰
۴۲	TC-R3440 Spec:I/B/N/H/C/V4.0		Up to 40-ch IP camera accesses Incoming/Outgoing bandwidth: 400Mbps/400Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×16 Up to 16 channels-ch synchronous playback ·4 HDD. Up to 10 TB capacity for each HDD. Independent HDMI and VGA outputs HDMI output at up to 4K resolution 2xRJ-45, 10/100/1000 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade	۴۳۳,۶۰۰,۰۰۰