

Tiandy

آذر ۱۴۰۴

هیچ نیازی از سوی کاربر بی پاسخ نمی ماند

NETWORK CAMERA - NVR
TIANDY



تارتن دژ آریانا
CCTV AND SECURITY SYSTEMS

☎ ۰۲۱-۵۲۶۰۵

www.tiandy-cctv.com

BULLET SERIES

AK



TC-C321N
Spec:I3/E/Y/2.8mm

- Max. Resolution: 2MP
- Image Sensor: 1/3" CMOS
- Min. Illumination: Color: 0.04 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Plastic + Metal
- Video Analytics: Tripwire; Perimeter

23,000,000 R

Spark



TC-C320N
Spec:I3/E/Y/2.8mm/V5.1

- Max. Resolution: 2MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic
- Video Analytics: Tripwire; Perimeter

32,000,000 R

AK



TC-C321N
Spec:AK/I3W/E/Y/2.8mm/V2.0

- Max. Resolution: 2MP
- Image Sensor: 1/3" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2 Warm Light
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic, Bullet type, IP67
- Video Analytics: Tripwire; Perimeter

35,000,000 R

WIFI



TC-C32WN
spec: I5/Y/WIFI/4MM/V4.0

- Max. Resolution: 2MP
- Image Sensor: 1/2.8" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 50 m
- Built-in Mic: Yes
- Alarm I/O: Not specified
- On-board Storage: MicroSD (up to 512 GB)
- Housing: Metal + Plastic, Bullet type, IP67
- Video Analytics: Tripwire, Perimeter detection, Motion detection, Mask alarm

48,000,000 R

Super lite



TC-C320N
Spec:I5W/E/Y/V4.2

- Max. Resolution: 2MP
- Image Sensor: 1/2.8" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2 Warm Light
- IR Distance: Up to 50 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic, bullet style, IP67
- Video Analytics: Tripwire, Perimeter

52,500,000 R

Spark



TC-C340N
Spec:I3/E/Y/2.8MM(4mm)/V5.0

- Max. Resolution: 4MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic, Bullet type, IP67
- Video Analytics: Tripwire, Perimeter

55,500,000 R

Super lite




TC-C32GS
I5/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512 GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

59,000,000 R

Super lite



TC-C34GN
Spec:I5/E/Y/C/2.8mm/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : 0.02Lux
- Wide Dynamic Range : DWDR
- IR range up to 50m
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

59,700,000 R

Super lite



TC-C34GS
I5/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

69,000,000 R

Super lite



TC-C340N
Spec:I5W/E/Y/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : 120db WDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

71,000,000 R

Spark



TC-C32RN
Spec:I5/E/Y/QX/2.8mm/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/3"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 6
- IR Distance : Up to 50m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Plastic housing
- Video Analytics : Motion Detection

85,500,000 R



BULLET SERIES

Lite



TC-C35WP 3FRA-28

- Max. Resolution : 5MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.0004Lux
- Wide Dynamic Range : 120 db WDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 15m
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Human/Vehicle Classification; Tripwire; Perimeter

تماس بگیرید

Lite



TC-C38WS
Spec:I5/E/Y/M/2.8mm/V4.0

- Max. Resolution : 8MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal housing
- Video Analytics : Human/Vehicle Classification; Tripwire; Perimeter

145,000,000 R

Pro



TC-C35US
SPEC:I8/A/E/Y/M/C/H/2.7-13.5MM

- Max. Resolution : 5MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 4
- IR Distance : Up to 80m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal housing
- Video Analytics Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal

155,000,000 R

Pro



TC-C35TS
Spec:I8/A/E/Y/M/H/2.7-13.5mm/V4.1

- Max. Resolution : 5MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 4
- IR Distance : Up to 80m
- Built-in Mic : YES
- Alarm I/O : YES
- On-board Storage : microSD up to 512GB
- Housing : Metal housing
- Video Analytics Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; Heatmap; Loitering; Running; Parking; People Counting; Crowded Detection; Safety Helmet Detection; On Duty Detection; Video Abnormal; Audio Abnormal

تماس بگیرید

Pro



TC-C35WQ
Spec:I5W/E/Y/2.8mm/V4.2

- Max. Resolution :Up to 5MP,2880×1620@30fps
- Image Sensor : 1/2.7"CMOS
- Min. Illumination :Color:0.002Lux@(F1.6,AGC ON),B/W:0Lux with IR
- Wide Dynamic Range : 120dB
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : 1×Built-in Mic
- Alarm I/O : yes
- On-board Storage : Support microSD/microSDHC/microSDXC card,up to 512GB
- Housing : Metal housing
- Video Analytics :Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal

تماس بگیرید



AK



TC-C320N

Spec:I3/E/Y/2.8mm

- Max. Resolution : 2MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : N/A

23,000,000 R

Spark



TC-C32XN

Spec:I3/E/Y/2.8mm/V5.1

- Max. Resolution : 2MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+Plastic Housing
- Video Analytics : N/A

32,000,000 R

AK



TC-C320N

Spec:AK/I3W/E/Y/2.8mm/V2.0

- Max. Resolution : 2MP
- Image Sensor : 1/3"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Plastic housing
- Video Analytics : Motion Detection - IP Address Conflict

35,000,000 R

Super lite



TC-C32XN

Spec:I3W/E/Y/2.8mm/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

51,000,000 R

Lite



TC-C32XP

Spec:I3W/E/Y/2.8mm/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : 120dB
- IR LEDs : 2 Warm Light
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : MicroSD up to 512GB
- Housing : Metal+Plastic Housing
- Video Analytics : Tripwire;Perimeter

49,000,000 R

WIFI



TC-C32KN

spec:I3/Y/WIFI/2.8MM

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 8
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire;Perimeter

50,000,000 R

Spark



TC-C34XN

Spec:I3/E/Y/2.8MM/V5.0

- Max. Resolution : 4MP
- Image Sensor : 1/3"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+Plastic Housing
- Video Analytics : Tripwire;Perimeter

54,500,000 R

Super lite



TC-C34HN

I3/E/Y/C/2.8mm/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

58,000,000 R

Super lite



TC-C34HS

I3/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

61,000,000 R

Super lite



TC-C34XN

Spec:I3W/E/Y/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : 120dB
- IR LEDs : 2 Warm Light
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

69,500,000 R

Super lite



TC-C34KS

Spec:I3/E/Y/2.8mm

- Max. Resolution : 4MP
- Image Sensor : 1/2.8" CMOS
- Min. Illumination : Color: 0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 8
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : MicroSD up to 512 GB
- Housing : Metal+Plastic Housing
- Video Analytics : Tripwire, Perimeter

79,000,000 R

Lite



TC-C35KS

Spec:I3/E/Y/2.8mm/v4.0

- Max. Resolution : 5MP
- Image Sensor : 1/2.8" CMOS
- Min. Illumination : Color: 0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 8
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : MicroSD up to 512 GB
- Housing : Metal+Plastic Housing
- Video Analytics : Tripwire, Perimeter

89,000,000 R



Lite



TC-C38XS
Spec: I3/E/Y/M/2.8mm/V4.0

- Max. Resolution : 8MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal housing
- Video Analytics : ripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Parking, Crowded, People Counting, On Duty Detection, Video Abnormal, Audio Abnormal, Heatmap, Safety Helmet Detection, Human/Vehicle Classification

109,000,000 R

Pro



TC-C35MS
SPEC:I3/A/E/Y/M/C/H/2.7- 13.5MM/V4.0

- Max. Resolution : 5MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 18
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : Yes
- On-board Storage : microSD to 512GB
- Housing : Metal+plastic housing
- Video Analytics :Tripwire; Perimeter

129,500,000 R

Pro



TC-C35MS
Spec:I5/A/E/Y/M/H/2.7-13.5mm/V4.1

- Max. Resolution : 5MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 18
- IR Distance : Up tp 50m
- Built-in Mic : YES
- Alarm I/O : Yes
- On-board Storage : microSDup to 512GB
- Housing : Metal housing
- Video Analytics :Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; Heatmap; Loitering; Running; Parking; People Counting; Crowded Detection; Safety Helmet Detection; On Duty Detection; Video Abnormal; Audio Abnormal

تماس بگیریڊ

Pro



TC-C38MS
SPEC:I5/A/E/Y/M/H/2.7-13.5mm/V4.0

- Max. Resolution : 8MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination :Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 18
- IR Distance : Up tp 50m
- Built-in Mic : YES
- Alarm I/O : Yes
- On-board Storage : microSD up to 512GB
- Housing : Metal housing
- Video Analytics :Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; Heatmap; Loitering; Running; Parking; People Counting; Crowded Detection; Safety Helmet Detection; On Duty Detection; Video Abnormal; Audio Abnormal

تماس بگیریڊ

SPEED-DOME SERIES



TC-H324S
Spec:23X/I/E/C/V3.0

- 2MP
- Up to 1920X1080@30fps
- Optical zoom: 23x
- Smart IR, IR Range: 150m
- S+265/H.265/H.264/M-JPEG
- Intelligent monitoring
- Support Human/Vehicle Classification
- Plugin Free
- IP66

299,000,000 R



TC-H324S
SPEC:25X/I/E/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5
- Optical zoom: 25x, digital zoom 16x
- Support Human/Vehicle Classification
- Smart IR,
- IR Range: 150m S+265/H.265/H.264/M-JPEG Plugin Free
- IP66

475,000,000 R



TC-H344S
Spec:25X/I/E+/A/V3.0

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),B/W:0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG
- Optical zoom 25X
- IR range up to 150m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -30°C~65°C(-22°F~149°F), ≤95%RH
- DC12V±10%, PoE:IEEE 802.3at
- IP66

550,000,000 R



TC-H326S
SPEC:33X/I/E+/A/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5 -
- Optical zoom: 33x, digital zoom 16x -
- Smart IR,
- IR Range: 200m - S+265/H.265/H.264/M-JPEG - Intelligent monitoring/ Face Capture mode Support Human/Vehicle Classification - Support Auto-tracking
- Plugin Free - IP66

669,000,000 R



TC-H366V
Spec:4MP/25X/IW/E/A/2.8mm

- 6MP
- Detail:2560×1440@25fps
- Panorama:0.0001lux Detail:0.001Lux
- Panorama:S+265/H.265/H.264/M-JPEG
- Detail:S+265/H.265/H.264/M-JPEG
- Built-in Micro SD card slot, up to 512 GB
- Support Panorama:Smart surveillance Detail:Smart surveillance
- Support Panorama:Human/Vehicle Classification
- Detail:Human/Vehicle Classification
- Operating Conditions -30°C~65°C(IR OFF) -30°C~
- 40°C(IR ON), 0-95%
- AC24V±25%\DC24V±10%, POE IEEE802.3BT
- IP66

850,000,000 R



TC-H356S
SPEC:30X/I/E++/A/V3.0

- 5MP
- Support Auto-tracking Up to 2880×1620@30fps Min. illumination Color: 0.001Lux@F1.5 Optical zoom:
- 30×digital zoom 16x
- Smart IR, IR Range: 200m
- S+265/H.265/H.264/M-JPEG
- Intelligent monitoring/ Face Capture mode Support Human/Vehicle Classification Plugin Free IP66

880,000,000 R




TC-H348M
Spec:63X/IL/E++/A

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H
- Optical zoom 63X
- IR range up to 300m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -40°C~70°C(-40°F~158°F), ≤95%RH
- DC36V±25%, PoE:IEEE 802.3bt
- IP66

تماس بگیرید





TC-R3105
Spec:I/B/L/S

- Up to 5-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 5MP(30fps)×1 or 1080P(30fps)×2
- 4-ch synchronous playback
- Up to 6 TB capacity for each HDD
- 1×HDMI output
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

52,500,000 R



TC-R3108
Spec:I/B/V2.0

- Up to 8-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4
- 4-ch synchronous playback
- Up to 8 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- PoE interface, 8×RJ45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

56,000,000 R



TC-R3104
Spec:I/B/P4/C/Eu/L/S/V2.0

- Up to 4-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4
- 4-ch synchronous playback
- Up to 8 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- PoE interface, 4×RJ45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

56,000,000 R



TC-R3105
SPEC:I/B/P/L

- S+265/H.265/H.264 video formats • Connectable to the third-party network cameras • Support live view, storage, and playback of the connected camera at up to 6MP resolution
- 1 SATA interface, up to 8TB for 1 HDD • S+265 compression effectively reduces the storage space and costs by up to 75%
- 1×HDMI and 1×VGA simultaneous outputs • HDMI Video output at up to 4K resolution

61,000,000 R



TC-R3110
Spec:I/B/L/S/Eu

- Up to 10-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4
- Up to 4 channels-ch synchronous playback
- Up to 8 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

69,000,000 R



TC-R3108
Spec: I/B/P8/C/Eu/L/S

- Up to 8-channel input
- 8 PoE ports
- Up to 6MP Resolution Recording

69,500,000 R



TC-R3120
Spec:I/B/V3.0

- HD Input
- +265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 20-channel input
- Supports live view, storage, and playback of the connected camera at up to 8MP resolution

136,900,000 R



TC-R3220
Spec:I/B/K/V3.1

- Up to 20-ch IP camera accesses Incoming/Outgoing bandwidth: 160Mbps/64Mbps S+265, H.265, S+264, H.264 video formats Max. decoding capability: 8MP(30fps)×2 or 1080P(30fps)×8 Up to 16 channels-ch synchronous playback Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs HDMI output at up to 4K resolution 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port S+ 265 compression effectively reduces the storage space by up to 75% Support cloud upgrade

249,000,000 R



TC-R3232
Spec:I/B/K/V3.1

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps/48Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 8MP(30fps)×2 or 1080P(30fps)×8
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

290,000,000 R



TC-R3432
Spec:I/B/K/V3.1

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps/48Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 8MP(30fps)×2 or 1080P(30fps)×8
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

390,000,000 R



TC-R3440
Spec:I/B/N/H/C/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×16
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- 16-ch synchronous playback
- Support cloud upgrade
- Up to 10 TB capacity for each HDD

475,000,000 R



TC-R3440
Spec:I/B/N/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×16
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- 16-ch synchronous playback
- Support cloud upgrade
- Up to 10 TB capacity for each HDD

590,000,000 R





TC-R3880

Spec:I/B/N/V4.0

- HD Input HD Transmission
S+265/H.265/H.264 video formats
Connectable to the third-party network
cameras Up to 80 IP cameras can be
connected Supports live view, storage, and
playback of the connected camera at up to
12MP resolution HD Output HDMI and VGA
independent outputs HDMI Video output at up
to 4K (3840 X 2160) resolution HD Storage 8
SATA interfaces connectable for recording
and backup, up to 10TB for each HDD S+265
compression effectively reduces the storage
space and costs by up to 75% 2 self-adaptive
10/100/1000 Mbps network interfaces

تماس بگیرید

