


Tiandy

اردیبهشت 1405

هیچ نیازی از سوی کاربر بی پاسخ نمی ماند

NETWORK CAMERA - NVR
TIANDY



BULLET SERIES

AK



TC-C321N
Spec:I3/E/Y/2.8mm

- Max. Resolution: 2MP
- Image Sensor: 1/3" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Plastic + Metal
- Video Analytics: Tripwire; Perimeter

66,000,000 R

AK



TC-C321N 1CNB-28

- Max. Resolution : 2MP
- Image Sensor : 1/3" CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : N/A

68,000,000 R

AK



TC-C321N
Spec:AK/I3W/E/Y/2.8mm/V2.0

- Plastic housing
- Up to 2MP,1920×1080@30fps
- S+265/H.265/H.264B/H.264M/H.264H
- Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
- IR range up to 30m
- 1×Built-in Mic
- Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH
- PoE:IEEE 802.3af,Max. 3W
- IP67

79,000,000 R

AK



TC-C321N 1ANB-28

- Max. Resolution : 2MP
- Image Sensor : 1/3"CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- **Dual light + 15m White LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Video Analytics : N/A

79,000,000 R

Spark



TC-C32QN
Spec:I3/E/Y/2.8mm/V5.1

- Max. Resolution: 2MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic
- Video Analytics: Tripwire; Perimeter

79,350,000 R

Spark



TC-C32QN
Spec:I5W/E/Y/V4.2

- Metal+plastic housing
- Up to 2MP,1920×1080@30fps
- S+265/H.265/H.264B/H.264M/H.264H
- Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
- IR range up to 50m
- 1×Built-in Mic
- Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH
- DC12V±25%,Max. 6.5W, PoE:IEEE 802.3af,Max. 7W
- IP67

105,000,000 R

Spark



TC-C34QN
Spec:I3/E/Y/2.8MM(4mm)/V5.0

- Max. Resolution: 4MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic, Bullet type, IP67
- Video Analytics: Tripwire, Perimeter

113,620,000 R

Super lite




TC-C32GS
I5/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512 GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

103,000,000 R

Super lite



TC-C34GN
Spec:I5/E/Y/C/2.8mm/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : 0.02Lux
- Wide Dynamic Range : DWDR
- IR range up to 50m
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

117,300,000 R

Super lite



TC-C34QN
Spec:I5W/E/Y/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : 120db WDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

147,000,000 R

Super lite



TC-C34GS
I5/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

142,800,000 R


Lite



TC-C35WS 3ERA-28

- Max. Resolution : 5MP
- Image Sensor : 1/2.7" CMOS
- Min. Illumination :Color:0.002Lux
- Wide Dynamic Range : 120 db
- IR LEDs : 2
- IR Distance : Up to 50m
- **Dual light + 15m white LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : **Metal housing**
- Video Analytics : Human/Vehicle Classification; Tripwire; Perimeter

230,000,000 R



BULLET SERIES

Pro



TC-C35US

Spec:I8/A/E/Y/M/S/H/2.7-13.5mm/V4.0

- Max. Resolution :Up to 5MP,2880×1620@30fps
- Image Sensor : 1/2.7"CMOS
- Min. Illumination :Color:0.002Lux@(F1.6,AGC ON),B/W:0Lux with IR
- Wide Dynamic Range : 120dB
- IR LEDs : 4
- IR Distance : Up to 80m
- Built-in Mic : 1×Built-in Mic
- Alarm I/O : yes
- On-board Storage : Support microSD/microSDHC/microSDXC card,up to 512GB
- Housing : Metal housing
- Video Analytics :Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal

330,000,000 R

WIFI




TC-H332A

Spec:I2W/WIFI/Eu/4mm


- Max. Resolution : 3MP
- Image Sensor : 1/3"CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 4
- IR Distance : Up to 15m
- **Dual light + 8m white LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Plastic housing
- Video Analytics : Smart Alarm

102,925,000 R



DOMESERIES

AK  TC-C320N <u>Spec:I3/E/Y/2.8mm</u> - Max. Resolution : 2MP - Image Sensor : 1/2.9"CMOS - Min. Illumination : Color:0.02Lux - Wide Dynamic Range : DWDR - IR LEDs : 2 - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Metal+plastic housing - Video Analytics : N/A 66,000,000 R	AK  TC-C320N 1CNB-28 - Max. Resolution : 2MP - Image Sensor : 1/3"CMOS - Min. Illumination :Color:0.02Lux - Wide Dynamic Range : DWDR - IR LEDs : 2 - IR Distance : Up to 30m - Built-in Mic : 1YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Plastic housing - Video Analytics : N/A 68,000,000 R	AK  TC-C320N <u>Spec:AK/I3W/E/Y/2.8mm/V2.0</u> - Plastic housing - Up to 2MP,1920×1080@30fps - S+265/H.265/H.264B/H.264M/H.264H - IR LEDs : 2 - Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR - IR range up to 30m 1×Built-in Mic - Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH - PoE:IEEE 802.3af,Max. 2.5W 79,000,000 R	AK  TC-C320N 1ANB-28 - Max. Resolution : 2MP - Image Sensor : 1/3"CMOS - Min. Illumination :Color:0.02Lux - Wide Dynamic Range : DWDR - IR LEDs : 2 - IR Distance : Up to 30m Dual light + 15m white LED - Built-in Mic : 1YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Plastic housing - Video Analytics : N/A 79,000,000 R
Spark  TC-C32XN <u>Spec:I3/E/Y/2.8mm/V5.1</u> - Max. Resolution : 2MP - Image Sensor : 1/2.9"CMOS - Min. Illumination : color:0.02Lux - Wide Dynamic Range : DWDR - IR LEDs : 2 - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Metal+Plastic Housing - Video Analytics : N/A 85,000,000 R	Spark  TC-C32XN <u>Spec:I3W/E/Y/2.8mm/V4.2</u> - Metal+plastic housing - Up to Max. Resolution - S+265/H.265/H.264B/H.264M/H.264H - Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR - IR Range 30m - Built-in Mic - Support Smart surveillance - Operating Conditions -30°C~60°C(No turning on the - light), Humidity 95% or less (no condensation) - DC12V±25%,MAX 6.5W, POE 802.3af,MAX 7W 105,000,000 R	Spark  TC-C34XN <u>Spec:I3/E/Y/2.8MM/V5.0</u> - Max. Resolution : 4MP - Image Sensor : 1/3"CMOS - Min. Illumination : Color:0.02Lux - Wide Dynamic Range : DWDR - IR LEDs : 2 - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Metal+Plastic Housing - Video Analytics : Tripwire;Perimeter 117,000,000 R	Super lite  TC-C34HN <u>I3/E/Y/C/2.8mm/V4.2</u> - Metal+plastic housing - Up to 4MP,2688×1520@25fps - S+265/H.265/H.264B/H.264M/H.264H - Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR - IR range up to 30m 1×Built-in Mic - Operating conditions -30°C~60°C(-22°F~140°F), ≤95%RH - PoE:IEEE 802.3af,Max. 6W - IP66 112,000,000 R
Super lite  TC-C34XN <u>Spec:I3W/E/Y/2.8MM/V4.2</u> - Max. Resolution : 4MP - Image Sensor : 1/2.9"CMOS - Min. Illumination : Color:0.02Lux - Wide Dynamic Range : 120dB WDR - IR LEDs : 2 Warm Light - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : N/A - Housing : Metal+plastic housing - Video Analytics :Tripwire; Perimeter 143,000,000 R	Super lite  TC-C34KS <u>Spec:I3/E/Y/2.8mm</u> - Max. Resolution : 4MP - Image Sensor : 1/2.8" CMOS - Min. Illumination : Color: 0.002Lux - Wide Dynamic Range : 120dB WDR - IR LEDs : 8 - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : MicroSD up to 512 GB - Housing : Metal+Plastic Housing - Video Analytics : Tripwire, Perimeter 203,550,000 R	Lite  TC-C34XP <u>SPEC: W/E/Y/2.8MM/V4.0</u> - Max. Resolution : 4MP - Image Sensor : 1/2.8" CMOS - Min. Illumination : Color: 0.0008Lux@ (F1.0, ACG ON), 0Lux with LED on - Wide Dynamic Range : 120dB WDR - IR LEDs : N/A - IR Distance : - - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : MicroSD up to 512 GB - Housing : Metal+Plastic Housing - Video Analytics : Tripwire, Perimeter 201,250,000 R	Lite  TC-C35KS <u>Spec:I3/E/Y/2.8mm/v4.0</u> - Max. Resolution : 5MP - Image Sensor : 1/2.8" CMOS - Min. Illumination : Color: 0.002Lux - Wide Dynamic Range : 120dB WDR - IR LEDs : 8 - IR Distance : Up to 30m - Built-in Mic : YES - Alarm I/O : N/A - On-board Storage : MicroSD up to 512 GB - Housing : Metal+Plastic Housing - Video Analytics : Tripwire, Perimeter 228,000,000 R



DOMESERIES

Pro




TC-C35MS

SPEC:I3/A/E/Y/M/C/H/2.7- 13.5MM/V4.0

- Max. Resolution : 5MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 18
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : Yes
- On-board Storage : microSD to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

253,000,000 R



SPEED-DOME SERIES



TC-H324S
Spec:23X/I/E/C/V3.0

- 2MP
- Up to 1920X1080@30fps
- Optical zoom: 23x
- Smart IR, IR Range: 150m
- S+265/H.265/H.264/M-JPEG
- Intelligent monitoring
- Support Human/Vehicle Classification
- Plugin Free
- IP66

770,000,000 R



TC-H324S
SPEC:25X/I/E/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5
- Optical zoom: 25x, digital zoom 16x
- Support Human/Vehicle Classification
- Smart IR,
- IR Range: 150m S+265/H.265/H.264/M-JPEG Plugin Free
- IP66

1,050,000,000 R



TC-H326S
SPEC:33X/I/E+/A/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5
- Optical zoom: 33x, digital zoom 16x
- Smart IR,
- IR Range: 200m - S+265/H.265/H.264/M-JPEG - Intelligent monitoring/ Face Capture mode Support Human/Vehicle Classification - Support Auto-tracking
- Plugin Free - IP66

1,400,000,000 R



TC-H366V
Spec:4MP/25X/IW/E/A/2.8mm

- 6MP
- Detail:2560x1440@25fps
- Panorama:0.0001lux Detail:0.001Lux
- Panorama:S+265/H.265/H.264/M-JPEG
- Detail:S+265/H.265/H.264/M-JPEG
- Built-in Micro SD card slot, up to 512 GB
- Support Panorama:Smart surveillance Detail:Smart surveillance
- Support Panorama:Human/Vehicle Classification
- Detail:Human/Vehicle Classification
- Operating Conditions -30°C~65°C(IR OFF) -30°C~40°C(IR ON), 0-95%
- AC24V±25%\DC24V±10%, POE IEEE802.3BT
- IP66

1,725,000,000 R



TC-H344S
Spec:25X/I/E+/A/V3.0

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),B/W:0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG
- Optical zoom 25X
- IR range up to 150m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -30°C~65°C(-22°F~149°F), ≤95%RH
- DC12V±10%, PoE:IEEE 802.3at
- IP66


1,220,000,000 R



TC-H348M
Spec:63X/IL/E++/A

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H
- Optical zoom 63X
- IR range up to 300m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -40°C~70°C(-40°F~158°F), ≤95%RH
- DC36V±25%, PoE:IEEE 802.3bt
- IP66

تماس بگیرید



NVR SERIES



TC-R3104

Spec:I/B/P4/C/Eu/L/S/V2.0

- Up to 4-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4
- 4-ch synchronous playback
- Up to 8 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- PoE interface, 4×RJ45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

159,000,000 R



TC-R3105

Spec:I/B/L/S

- Up to 5-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 5MP(30fps)×1 or 1080P(30fps)×2
- 4-ch synchronous playback
- Up to 6 TB capacity for each HDD
- 1×HDMI output
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

125,350,000 R



TC-R3108

Spec: I/B/P8/C/Eu/L/S

- Up to 8-channel input
- 8 PoE ports
- Up to 6MP Resolution Recording

185,000,000 R



TC-R3120

Spec:I/B/V3.0

- HD Input
- +265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 20-channel input
- Supports live view, storage, and playback of the connected camera at up to 8MP resolution

313,950,000 R



TC-R3220 4HA

AI NVR

- Up to 20-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps(AI on: 120Mbps)/80Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×1 or 1080P(30fps)×10
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

630,000,000 R



TC-R3232 4HA

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps(AI on: 120Mbps)/80Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×1 or 1080P(30fps)×10
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

747,500,000 R



TC-R3432

Spec:I/B/K/V3.1

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps/48Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 8MP(30fps)×2 or 1080P(30fps)×8
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

880,000,000 R



TC-R3240

Spec:I/B/N/H/V4.1

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

890,000,000 R



TC-R3440

Spec:I/B/N/H/C/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Up to 10 TB capacity for each HDD

980,000,000 R



TC-R3440

Spec:I/B/N/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Up to 10 TB capacity for each HDD

1,200,000,000 R



TC-R3840

Spec:I/B/N/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 640Mbps/320Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×4 or 1080P(30fps)×32
- 16-ch synchronous playback
- Up to 24 TB capacity for each HDD
- Simultaneous HDMI1 and VGA1 outputs; Simultaneous HDMI2 and VGA2 outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

تماس بگیرید



TC-R3880

Spec:I/B/N/V4.0

- HD Input HD Transmission
- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras Up to 80 IP cameras can be connected Supports live view, storage, and playback of the connected camera at up to 12MP resolution HD Output HDMI and VGA independent outputs HDMI Video output at up to 4K (3840 X 2160) resolution HD Storage 8 SATA interfaces connectable for recording and backup, up to 10TB for each HDD S+265 compression effectively reduces the storage space and costs by up to 75% 2 self-adaptive 10/100/1000 Mbps network interfaces

تماس بگیرید

